




CODE No.	CONTACT	A	B	C	D	E	F	G
CL537-0003-6-86	20	7. 1	4. 5	5. 2	5. 6	6. 6	5. 3	8. 1
CL537-0005-1-86	30	9. 6	7. 0	7. 7	8. 1	9. 1	7. 8	10. 6
CL537-0012-7-86	32	10. 1	7. 5	8. 2	8. 6	9. 6	8. 3	11. 1
CL537-0006-4-86	36	11. 1	8. 5	9. 2	9. 6	10. 6	9. 3	12. 1
CL537-0007-7-86	40	12. 1	9. 5	10. 2	10. 6	11. 6	10. 3	13. 1
CL537-0009-2-86	50	14. 6	12. 0	12. 7	13. 1	14. 1	12. 8	15. 6
CL537-0011-4-86	60	17. 1	14. 5	15. 2	15. 6	16. 6	15. 3	18. 1

RECOMMEND METAL MASK PATTERN (10:1)

RECOMMENDED LAND PATTERN (10:1)

RECOMMENDED THICKNESS OF
SOLDER PASTE : 120 μm

NOTES 1 LEAD CO-PLANARITY SHALL BE 0.08 mm MAX.
 2 IF THERE IS PATTERN ON  PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE LEADS.
 3 REINFORCED METAL FITTINGS AS FOLLOWS.

				7	PS	CLEAR (REINFORCEMENT COLLAR)				
				6	PS	BLACK (PLASTIC REEL)				
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2#m min LEAD AREA:GOLD PLATED 0.015#m min OTHERS(UNDER PLATING):NICKEL PLATED 2#m min			5	POLYESTER	CLEAR (COVER TAPE)			
					4	PS	CLEAR (EMBOSSSED CARRIER TAPE)			
					3	BRASS	TIN PLATED 2#m min (UNDER PLATING):NICKEL 1#m min			
1	POLYAMIDE	UL94V-0・NATURAL (BEIGE)								
NO.	MATERIAL	FINISH . REMARKS			NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 5 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-H-00001678		DESIGNED SH. HOSODA	CHECKED TS. MIYAZAKI	DATE 16. 05. 30	
 HIROSE ELECTRIC CO., LTD.		APPROVED : KH. IKEDA	13. 08. 06		DRAWING NO.		EDC3-162502-77			
		CHECED : YH. MICHIDA	13. 08. 06		PART NO.		DF12-*DS-0. 5V (86)			
		DESIGNED : YN. SAKAMOTO	13. 08. 05		CODE NO.		CL537			
		DRAWN : KR. AJITO	13. 08. 05				 1/2			

